


| PART NO.   | CONDUCTOR MATERIAL | CURRENT   |
|------------|--------------------|-----------|
| FA11644    | COPPER             | 27 AMPS   |
| FA11644-02 | MOLYBDENUM         | 13.5 AMPS |
| FA11644-03 | NICKEL             | 8.2 AMPS  |
| FA11644-04 | 304 STN STL        | 1.8 AMPS  |

| RATINGS      |                   |
|--------------|-------------------|
| VOLTAGE:     | 3 KV DC           |
| CURRENT:     | SEE TABLE AT LEFT |
| PRESSURE:    | 1250 PSIG @ 20°C  |
| TEMPERATURE: | -269°C TO 450°C   |

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

TWO 3KV FEEDTHROUGHS

[WWW.SOLIDSEALING.COM](http://WWW.SOLIDSEALING.COM)



**SOLID SEALING TECHNOLOGY, INC.**

| REV. | APP'D | DATE       | SCALE 1:1    | DIMENSIONS IN INCHES [mm] | DRAWN     | JM | 1/12/2006  |
|------|-------|------------|--------------|---------------------------|-----------|----|------------|
| A2   | JS    | 05/02/2013 | MPCL0016-0ST |                           | ENG APPR. | MH | 03/21/2006 |

PART NO. (SEE TABLE) REV. A

SALES DWG NO. FA11644SL REV. A2

**DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.**