



PLUGS SOLD SEPARATELY:
 -VACUUM SIDE PEEK PLUG FA13461
 -AIR SIDE W/ SOLDER CONTACTS FP14900
 -AIR SIDE W/CRIMP CONTACTS KT14378

RATINGS	
VOLTAGE:	1KV DC
CURRENT:	5 AMPS
PRESSURE:	450 PSIG @ 20°C
TEMPERATURE:	-269°C TO 450°C

WWW.SOLIDSEALING.COM



SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA12933SL REV. D1

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

10 PIN CONNECTOR

PART NO. FA12933 REV. D

REV.	APP'D	DATE	SCALE 2.5:1	DIMENSIONS IN INCHES [mm]	DRAWN	JM	4/19/2006
D1	JF	08/07/2017	MPCL0055-01SL		ENG APPR.	MH	06/26/2006

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.