

PART NO.	CONDUCTOR MATERIAL	CURRENT
FA13481	COPPER	16 AMPS
FA13481-02	MOLYBDENUM	8.5 AMPS
FA13481-03	NICKEL 200	5.0 AMPS
FA13481-04	304 STN STL	1.1 AMPS

RATINGS	
VOLTAGE:	1KV DC
CURRENT:	SEE TABLE AT LEFT
PRESSURE:	3500 PSIG @ 20°C
TEMPERATURE:	-80°C TO 450°C*

*CALL SST TO CONFIRM LOWER TEMPERATURE USE

WWW.SOLIDSEALING.COM




SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA13481SL REV. A3

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

1KV FEEDTHRU

PART NO. (SEE TABLE) REV. A

REV.	APP'D	DATE	SCALE 3:1	DIMENSIONS IN INCHES [mm]	DRAWN	OG	08/15/2005
A3	JS	05/20/2013	FCLO052-0ST		ENG APPR.	OG	08/15/2005

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.