

PLUGS SOLD SEPARATELY:
 - VACUUM SIDE PEEK PLUG FA13604
 - AIR SIDE PLUG KT14877

| RATINGS | |
|-------------|----------------|
| VOLTAGE | 500 V DC |
| CURRENT | 5 AMPS |
| PRESSURE: | 0 PSIG @ 20°C* |
| TEMPERATURE | -25°C TO 205°C |

*FOR INTERNAL PRESSURE 5 TO 100 PSIG
 AN OVERPRESSURE RING IS REQUIRED.

WWW.SOLIDSEALING.COM




SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA14980SL REV. A3

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

15 PIN SUB-D CONNECTOR

PART NO. FA14980 REV. A

| REV. | APP'D | DATE | SCALE 1:1 | DIMENSIONS IN INCHES [mm] | DRAWN | MH | 02/28/2008 |
|------|-------|------------|-------------|---------------------------|-----------|----|------------|
| A3 | JS | 11/21/2012 | MPCL0121-01 | | ENG APPR. | MH | 02/28/2008 |

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.