

PLUGS SOLD SEPARATELY:
 -VACUUM SIDE PEEK PLUG FA13462
 -AIR SIDE W/SOLDER CONTACTS FP14901
 -AIR SIDE W/CRIMP CONTACTS KT14379

| RATINGS | |
|--------------|----------------|
| VOLTAGE: | 1KV DC |
| CURRENT: | 3 AMPS |
| PRESSURE: | 0 PSIG @ 20°C* |
| TEMPERATURE: | -25°C TO 205°C |

*FOR INTERNAL PRESSURE 5 TO 100 PSIG AN OVERPRESSURE RING IS REQUIRED.

WWW.SOLIDSEALING.COM




SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA15138SL REV. B1

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

19 PIN CONNECTOR

PART NO. FA15138 REV. B

| REV. | APP'D | DATE | SCALE 1:1 | DIMENSIONS IN INCHES [mm] | DRAWN | JS | 6/5/2008 |
|------|-------|------------|---------------|---------------------------|-----------|----|------------|
| B1 | JF | 08/04/2017 | MPCL0101-02SL | | ENG APPR. | MH | 07/08/2008 |

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.