


PART NO.	CONDUCTOR MATERIAL	CURRENT	AIR SIDE PLUG
FA15673	NICKEL	16 AMPS	NO
KT15673	NICKEL	16 AMPS	YES
FA15673-02	MOLYBDENUM	23 AMPS	NO
KT15673-02	MOLYBDENUM	23 AMPS	YES

RATINGS	
VOLTAGE:	700V DC
CURRENT:	SEE TABLE AT LEFT
PRESSURE:	475 PSIG @ 20°C
TEMPERATURE WITHOUT PLUG:	-269°C TO 450°C
TEMPERATURE WITH PLUG:	-55°C TO 125°C

WWW.SOLIDSEALING.COM

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE
 SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY
 REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN
 PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

TWO PIN CONNECTOR



SOLID SEALING TECHNOLOGY, INC.

REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	JS	1/15/2009
A2	JS	11/26/2012	MPDP0024-3ST		ENG APPR.	MH	01/15/2009

PART NO. (SEE TABLE) REV. A

SALES DWG NO. FA15673SL REV. A2

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.