



RATINGS	
# OF CONDUCTORS	9
VOLTAGE:	600V RMS/ 2KV DC
CURRENT:	5.5 AMPS PER CONDUCTOR
TEMPERATURE:	-55°C TO 200°C

CABLE IS AVAILABLE IN ANY LENGTH, PART NUMBER SUFFIX INDICATES LENGTH IN INCHES.

EXAMPLE: FA16652-033 IS A 33 INCH LONG CABLE.

WWW.SOLIDSEALING.COM

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 			TITLE: 22 AWG RIBBON CABLE		
REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	JS	5/16/2008	PART NO. FA16652 REV. A	
A2	JS	06/29/2012	AHDWR004-12		ENG APPR.	MH	07/11/2008		SALES DWG NO. FA16652SL REV. A2

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.