

PLUGS SOLD SEPARATELY:
 -VACUUM SIDE PEEK PLUG FA13605
 -AIR SIDE PLUG KT14878

| RATINGS | |
|--------------|----------------|
| VOLTAGE: | 500 V DC |
| CURRENT: | 3 AMPS |
| PRESSURE: | 0 PSIG @ 20°C* |
| TEMPERATURE: | -25°C TO 205°C |

*FOR INTERNAL PRESSURE 5 TO 100 PSIG
 AN OVERPRESSURE RING IS REQUIRED.

WWW.SOLIDSEALING.COM




SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA16712SL REV. A1

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE
 SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY
 REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN
 PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

(2) 25 PIN SUB-D CONNECTORS

PART NO. FA16712 REV. A

| REV. | APP'D | DATE | SCALE 2:3 | DIMENSIONS IN INCHES [mm] | DRAWN | JF | 05/20/2014 |
|------|-------|------------|-------------|---------------------------|-----------|----|------------|
| A1 | JF | 05/20/2014 | MPC10340-11 | | ENG APPR. | JF | 05/20/2014 |

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.