

PLUGS SOLD SEPARATELY:
 - AIR SIDE W/SOLDER CONTACTS FP18066
 - AIR SIDE W/ CRIMP CONTACTS KT18065

RATINGS	
VOLTAGE:	1 KV DC
CURRENT:	5 AMPS
PRESSURE:	500 PSIG @ 20°C
TEMPERATURE:	-269°C TO 450°C

WWW.SOLIDSEALING.COM




SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA19341SL REV. A2

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

6 PIN CONNECTOR

PART NO. FA19341 REV. A

REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	JS	8/26/2008
A2	JS	11/26/2012	MPCL0232-14SL		ENG APPR.	MH	11/19/2008

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.