

PART NO.	CONDUCTOR MATERIAL	CURRENT
FA23946	COPPER	27 AMPS
FA23946-02	MOLYBDENUM	13.5 AMPS
FA23946-03	NICKEL	8.2 AMPS
FA23946-04	304 STN STL	1.8 AMPS

RATINGS	
VOLTAGE:	3KV DC
CURRENT:	SEE TABLE AT LEFT
PRESSURE:	1250 PSIG @ 20°C
TEMPERATURE:	-260°C TO 230°C

WWW.SOLIDSEALING.COM




SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA23946SL REV. C1

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

FOUR 3KV FEEDTHROUGHS

PART NO. (SEE TABLE) REV. C

REV.	APP'D	DATE	SCALE 3:2	DIMENSIONS IN INCHES [mm]	DRAWN	JS	01/06/2011
C1	JF	05/19/2016	MPDC0019-2ST		ENG APPR.	JS	01/11/2011

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.