

PART NO.	CONDUCTOR MATERIAL	CURRENT WITH PLUG	CURRENT WITHOUT PLUG
FA24533	COPPER	100 AMPS	185 AMPS
FA24533-02	MOLYBDENUM	93 AMPS	93 AMPS
FA24533-03	NICKEL	56 AMPS	56 AMPS
FA24533-04	304 STN STL	12 AMPS	12 AMPS

PERFORMANCE SPECIFICATIONS		
	WITH PLUG	WITHOUT PLUG
VOLTAGE:	15KV DC	12KV DC
CURRENT:	SEE TABLE AT LEFT	SEE TABLE AT LEFT
PRESSURE:	0 PSIG @ 20°C*	0 PSIG @ 20°C*
TEMPERATURE:	-25°C TO 125°C	-25°C TO 205°C

\*FOR INTERNAL PRESSURE 5 TO 100 PSIG  
AN OVERPRESSURE RING IS REQUIRED.

MATES WITH POWERPLUG FA18649

[WWW.SOLIDSEALING.COM](http://WWW.SOLIDSEALING.COM)




**SOLID SEALING TECHNOLOGY, INC.**

SALES DWG NO. FA24533SL REV. A2

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

15KV FEEDTHRU

PART NO. (SEE TABLE) REV. A

REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	JS	04/01/2011
A2	JF	07/22/2016	FTST0145-1ST		ENG APPR.	JS	04/01/2011

**DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.**