

PART NO.	MATERIAL	IDENTIFICATION GROOVE	TEMPERATURE
KT10898	CHROMEL	YES	-269°C TO 350°C
KT10898-02	ALUMEL	NO	

NOTE: PACKAGE OF 5 CONTACTS

WWW.SOLIDSEALING.COM




SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. KT10898SL REV. B1

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

CONTACT CRIMP TYPE

PART NO. (SEE TABLE) REV. B

REV.	APP'D	DATE	SCALE 3:1	DIMENSIONS IN INCHES [mm]	DRAWN	MH	10/26/2006
B1	MH	04/29/2009	ACNCT001-ST		ENG APPR.	MH	10/27/2006

**DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.**