



PART NO.	MATERIAL	VACUUM RATING
KT13353	COPPER ALLOY GOLD FLASH	HIGH VACUUM
KT13353-02	CHROMEL	HIGH VACUUM
KT13353-03	ALUMEL	HIGH VACUUM
KT13353-11	COPPER ALLOY GOLD FLASH	ULTRA-HIGH VACUUM

RATINGS	
MATERIAL:	SEE TABLE AT LEFT
VACUUM RATING:	SEE TABLE AT LEFT
CURRENT:	7.5 AMPS
TEMPERATURE:	-65°C TO 200°C

NOTE: PACKAGE OF 5 CONTACTS

WWW.SOLIDSEALING.COM



SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. KT13353SL REV. F1

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

CRIMP CONTACT

PART NO. (SEE TABLE) REV. F

REV.	APP'D	DATE	SCALE 5:1	DIMENSIONS IN INCHES [mm]	DRAWN	MH	10/27/2006
F1	JF	11/01/2016	ACDCN010-1ST		ENG APPR.	JS	11/02/2011

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.