



RATINGS	
MATERIAL:	COPPER ALLOY GOLD FLASH
CURRENT:	7.5 AMPS
TEMPERATURE:	-55°C TO 125°C

NOTE: PACKAGE OF 5 CONTACTS

[WWW.SOLIDSEALING.COM](http://WWW.SOLIDSEALING.COM)



**SOLID SEALING TECHNOLOGY, INC.**

SALES DWG NO. KT14601SL REV. C1

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

SOCKET CONTACT

PART NO. KT14601 REV. C

REV.	APP'D	DATE	SCALE 4:1	DIMENSIONS IN INCHES [mm]	DRAWN	MH	01/30/2007
C1	JF	10/17/2018	ACDCN010-04		ENG APPR.	MH	01/30/2007

**DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.**