

RATINGS	
MATERIAL:	COPPER ALLOY GOLD FLASH
CURRENT:	7.5 AMPS
TEMPERATURE:	-55°C TO 125°C

NOTE: PACKAGE OF 5 CONTACTS

[WWW.SOLIDSEALING.COM](http://WWW.SOLIDSEALING.COM)




**SOLID SEALING TECHNOLOGY, INC.**

SALES DWG NO. KT14601SL REV. B2

PROPRIETARY AND CONFIDENTIAL  
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE: SOCKET CONTACT

REV.	APP'D	DATE	SCALE 4:1	DIMENSIONS IN INCHES [mm]
B2	MH	08/18/2008	ACDCN010-04	

DRAWN	MH	01/30/2007
ENG APPR.	MH	01/30/2007

PART NO. KT14601 REV. B

**DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.**