


| CONTACT MATERIAL: | LOCATIONS: |
|-------------------|------------|
| CHROMEL (+) | A,C |
| ALUMEL (-) | B,D |

| RATINGS | |
|--------------|----------------|
| THERMOCOUPLE | TYPE K |
| TEMPERATURE: | -55°C TO 125°C |

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

TYPE K 2 PAIR AIR SIDE PLUG

WWW.SOLIDSEALING.COM



SOLID SEALING TECHNOLOGY, INC.

| REV. | APP'D | DATE | SCALE 5:4 | DIMENSIONS IN INCHES [mm] | DRAWN | JS | 11/3/2008 |
|------|-------|------------|--------------|---------------------------|-----------|----|------------|
| A1 | MH | 11/04/2008 | MSME0003-01A | | ENG APPR. | MH | 11/04/2008 |

PART NO. KT19712 REV. A

SALES DWG NO. KT19712SL REV. A1

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.