

CONTACT MATERIAL:	LOCATIONS:
CHROMEL (+)	A,C,E,G,J,L,N,Q,S,U
ALUMEL (-)	B,D,F,H,K,M,P,R,T,V

RATINGS	
THERMOCOUPLE	TYPE K
TEMPERATURE:	-55°C TO 125°C

WWW.SOLIDSEALING.COM




SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. KT24173SL REV. A1

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

TYPE K 10 PAIR AIR SIDE PLUG

PART NO. KT24173 REV. A

REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	JS	01/19/2011
A1	JS	01/19/2011	MSME0050-13		ENG APPR.	JS	01/19/2011

**DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.**