

PART NO.	T/C TYPE	CONDUCTOR MATERIAL	COLOR
CP11728	K	CHROMEL / ALUMEL	YELLOW
CP11728-02	J	IRON / CONSTANTAN	BLACK
CP11728-03	С	TUNGSTEN / RHENIUM	RED
CP11728-04	Е	CHROMEL / CONSTANTAN	PURPLE

RATINGS				
T/C TYPE:	SEE TABLE AT LEFT			
TEMPERATURE:	-29°C TO 218°C			

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY, ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION

THERMOCOUPLE SPADE PLUG

SOLID SEALING TECHNOLOGY

 REV.
 APP'D
 DATE
 SCALE 2:1
 DIMENSIONS IN INCHES [mm]

 E1
 JF
 04/01/2020
 ACNPO042-ST
 INCHES [mm]

DRAWN MH 3/29/2006 ENG APPR. JF 04/01/2020

PART NO. (SEE TABLE) REV. E

WWW.SOLIDSEALING.COM

SALES DWG NO. CP11728SL REV. E1