

PART NO.	CONDUCTOR MATERIAL	CURRENT
FA10309	304 STN STL	3.6 AMPS
FA10309-02	COPPER	55 AMPS
FA10309-03	NICKEL	16.5 AMPS

RATINGS	
VOLTAGE:	30 KV DC
CURRENT:	SEE TABLE AT LEFT
PRESSURE:	250 PSIG @ 20°C
TEMPERATURE:	-80°C TO 450°C*

* CALL SST TO CONFIRM LOWER TEMPERATURE USE

WWW.SOLIDSEALING.COM




SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA10309SL REV. B2

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

30KV FLUTED FEEDTHROUGH

PART NO. (SEE TABLE) REV. B

REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	JM	1/6/2006
B2	JS	11/27/2012	FTFL0001-0ST		ENG APPR.	MH	03/21/2006

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.