

PART NO.	AIR SIDE PLUG
FA10313	NO
KT10313	YES

RATINGS	
VOLTAGE:	20KV DC
CURRENT:	16.5 AMPS
PRESSURE:	250 PSIG @ 20°C
TEMPERATURE WITHOUT PLUG:	-269°C TO 450°C
TEMPERATURE WITH PLUG:	-55°C TO 85°C

WWW.SOLIDSEALING.COM




SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA10313SL REV. B3

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE
SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY
REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN
PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

20KV SHV RECESSED CONNECTOR

PART NO. FA10313 REV. B

REV.	APP'D	DATE	SCALE 3:2	DIMENSIONS IN INCHES [mm]	DRAWN	JM	1/12/2006
B3	JS	10/22/2012	COS20001-02		ENG APPR.	MH	05/15/2006