


PART NO.	AIR SIDE PLUG
FA10326	NO
KT10326	YES

PERFORMANCE SPECIFICATIONS	
VOLTAGE:	500V DC
CURRENT:	3.6 AMPS
PRESSURE:	1400 PSIG @ 20°C
TEMPERATURE WITHOUT PLUG:	-269°C TO 450°C
TEMPERATURE WITH PLUG:	-65°C TO 165°C

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.



TITLE

BNC CONNECTOR



REV.	APP'D	DATE	SCALE 3:1	DIMENSIONS IN INCHES [mm]	DRAWN	JM	1/18/2006
E1	CW	6/3/2021	COBN0001-01		ENG APPR.	CW	6/3/2021

PART NO. FA10326 REV. E

WWW.SOLIDSEALING.COM

SALES DWG NO. FA10326SL REV. E1

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.