


PART NO.	AIR SIDE PLUG
FA10337	NO
KT10337	YES

PERFORMANCE SPECIFICATIONS	
VOLTAGE:	5KV DC
CURRENT:	3.6 AMPS
PRESSURE:	1400 PSIG @ 20°C
TEMPERATURE WITHOUT PLUG:	-269°C TO 450°C
TEMPERATURE WITH PLUG:	-65°C TO 165°C

PROPRIETARY AND CONFIDENTIAL  
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE  
PROJECTION



TITLE

MHV CONNECTOR



**SOLID SEALING**  
TECHNOLOGY

REV.	APP'D	DATE	SCALE 3:1	DIMENSIONS IN INCHES [mm]	DRAWN	JM	1/18/2006
D1	CW	6/2/2021	COMH0001-01		ENG APPR.	MH	05/15/2006

PART NO. FA10337 REV. D

WWW.SOLIDSEALING.COM

SALES DWG NO. FA10337SL REV. D1

**DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.**