


| PERFORMANCE SPECIFICATIONS |                 |
|----------------------------|-----------------|
| VOLTAGE:                   | 13KV DC         |
| PRESSURE:                  | 900 PSIG @ 20°C |
| TEMPERATURE:               | -269°C TO 450°C |

PROPRIETARY AND CONFIDENTIAL  
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.



TITLE  
 13KV CRYOGENIC ISOLATOR



| REV. | APP'D | DATE       | SCALE 2:1   | DIMENSIONS IN INCHES [mm] | DRAWN     | JM | 1/13/2006  |
|------|-------|------------|-------------|---------------------------|-----------|----|------------|
| A3   | JF    | 11/07/2023 | BRCL0001-02 |                           | ENG APPR. | MH | 06/06/2006 |

PART NO. FA10622 REV. A

WWW.SOLIDSEALING.COM

SALES DWG NO. FA10622SL REV. A3

**DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.**