



PART NO.	CONDUCTOR MATERIAL	CURRENT
FA10775	COPPER	800 AMPS
FA10775-03	NICKEL	240 AMPS
FA10775-04	304 STN STL	52 AMPS

RATINGS	
VOLTAGE:	8KV DC
CURRENT:	SEE TABLE AT LEFT
PRESSURE:	250 PSIG @ 20°C
TEMPERATURE:	-269°C TO 450°C

WWW.SOLIDSEALING.COM



SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA10775SL REV. C1

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

8KV FEEDTHROUGH

PART NO. (SEE TABLE) REV. C

REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	JM	1/6/2006
C1	JS	10/30/2012	FTCL0008-0ST		ENG APPR.	MH	04/28/2006

**DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.**