



RATINGS	
VOLTAGE:	20KV DC
PRESSURE:	60 PSIG @ 20°C
TEMPERATURE:	-269°C TO 450°C

WWW.SOLIDSEALING.COM



SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA10863SL REV. B2

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

VACUUM ISOLATOR

PART NO. FA10863 REV. B

REV.	APP'D	DATE	SCALE 1:1.5	DIMENSIONS IN INCHES [mm]	DRAWN	JS	8/18/2008
B2	JF	12/15/2015	BRCL0003-01		ENG APPR.	MH	03/02/2009

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.