

RATINGS	
VOLTAGE:	30KV DC
PRESSURE:	30 PSIG @ 20°C
TEMPERATURE:	-269°C TO 450°C

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION

TITLE:

VACUUM ISOLATOR

PART NO. FA10868 REV. A

REV.	APP'D	DATE	SCALE 7:16	DIMENSIONS IN INCHES [mm]
A3	JF	04/24/2014	BRCL0005-01	

DRAWN	JS	8/21/2008
ENG APPR.	MH	03/02/2009

SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA10868SL REV. A3

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.