


PART NO.	AIR SIDE PLUG
FA11083	NO
KT11083	YES

RATINGS	
PIN/SHIELD VOLTAGE:	5KV DC
SHIELD/GROUND VOLTAGE:	2.5 KV DC
CURRENT:	10 AMPS
PRESSURE:	400 PSIG @ 20°C
TEMPERATURE WITHOUT PLUG:	-269°C TO 450°C
TEMPERATURE WITH PLUG:	-65°C TO 165°C

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

FLOATING DBL ENDED 5KV SHV

[WWW.SOLIDSEALING.COM](http://WWW.SOLIDSEALING.COM)



SOLID SEALING TECHNOLOGY, INC.

REV.	APP'D	DATE	SCALE 3:2	DIMENSIONS IN INCHES [mm]	DRAWN	JS	08/28/2013
A1	JS	08/28/2013	COS50002-01		ENG APPR.	JS	08/28/2013

PART NO. FA11083 REV. A

SALES DWG NO. FA11083SL REV. A1