



PART NO.	CONDUCTOR MATERIAL	CURRENT WITH PLUG	CURRENT WITHOUT PLUG
FA11138	COPPER	30 AMPS	55 AMPS
FA11138-02	MOLYBDENUM	28 AMPS	28 AMPS
FA11138-03	NICKEL	16.5 AMPS	16.5 AMPS
FA11138-04	304 STN STL	3.6 AMPS	3.6 AMPS

PERFORMANCE SPECIFICATIONS		
	WITH PLUG	WITHOUT PLUG
VOLTAGE:	10KV DC	5KV DC
CURRENT:	SEE TABLE AT LEFT	SEE TABLE AT LEFT
PRESSURE:	1500 PSIG @ 20°C	1500 PSIG @ 20°C
TEMPERATURE:	-55°C TO 125°C	-269°C TO 450°C

MATES WITH POWERPLUG FP10884 & FP10884-02

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 		TITLE 10KV FEEDTHROUGH			
REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	JM	1/6/2006	PART NO. (SEE TABLE) REV. B	WWW.SOLIDSEALING.COM
B1	JF	04/20/2026	FTST0015-ST		ENG APPR.	MH	04/28/2006		SALES DWG NO. FA11138SL REV. B1

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.