

| PART NO. | AIR SIDE PLUG |
|----------|---------------|
| FA11152 | NO |
| KT11152 | YES |

| RATINGS | |
|---------------------------|------------------|
| VOLTAGE: | 1.5KV DC |
| CURRENT: | 3.6 AMPS |
| PRESSURE: | 1800 PSIG @ 20°C |
| TEMPERATURE WITHOUT PLUG: | -269°C TO 450°C |
| TEMPERATURE WITH PLUG: | -65°C TO 165°C |

WWW.SOLIDSEALING.COM




SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA11152SL REV. C2

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

TYPE N CONNECTOR

PART NO. FA11152 REV. C

| REV. | APP'D | DATE | SCALE 2:1 | DIMENSIONS IN INCHES [mm] | DRAWN | MH | 02/10/2006 |
|------|-------|------------|-------------|---------------------------|-----------|----|------------|
| C2 | JS | 10/19/2012 | COTN0001-01 | | ENG APPR. | MH | 05/15/2006 |

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.