


PART NO.	AIR SIDE PLUG
FA11152	NO
KT11152	YES

RATINGS	
VOLTAGE:	1.5KV DC
CURRENT:	3.6 AMPS
PRESSURE:	1800 PSIG @ 20°C
TEMPERATURE WITHOUT PLUG:	-269°C TO 450°C
TEMPERATURE WITH PLUG:	-65°C TO 165°C

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

TYPE N CONNECTOR

[WWW.SOLIDSEALING.COM](http://WWW.SOLIDSEALING.COM)



**SOLID SEALING TECHNOLOGY, INC.**

PART NO. FA11152 REV. C

SALES DWG NO. FA11152SL REV. C2

REV.	APP'D	DATE	SCALE 2:1	DIMENSIONS IN INCHES [mm]	DRAWN	MH	02/10/2006
C2	JS	10/19/2012	COTN0001-01		ENG APPR.	MH	05/15/2006