

| | |
|----------|---------------|
| PART NO. | AIR SIDE PLUG |
| FA11170 | NO |
| KT11170 | YES |

| RATINGS | |
|---------------------------|------------------|
| VOLTAGE: | 500V DC |
| CURRENT: | 3.6 AMPS |
| PRESSURE: | 1400 PSIG @ 20°C |
| TEMPERATURE WITHOUT PLUG: | -269°C TO 450°C |
| TEMPERATURE WITH PLUG: | -65°C TO 165°C |

WWW.SOLIDSEALING.COM




SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA11170SL REV. A2

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

THREE BNC CONNECTORS

PART NO. FA11170 REV. A

| REV. | APP'D | DATE | SCALE 1:1 | DIMENSIONS IN INCHES [mm] | DRAWN | JM | 1/18/2006 |
|------|-------|------------|-------------|---------------------------|-----------|----|------------|
| A2 | JS | 10/05/2012 | COBN0012-01 | | ENG APPR. | MH | 05/15/2006 |

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.