


PART NO.	AIR SIDE PLUG
FA11314	NO
KT11314	YES

PERFORMANCE SPECIFICATIONS	
VOLTAGE:	5KV DC
CURRENT:	3.6 AMPS
PRESSURE:	1400 PSIG @ 20°C
TEMPERATURE WITHOUT PLUG:	-269°C TO 450°C
TEMPERATURE WITH PLUG:	-65°C TO 165°C

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.



THIRD ANGLE PROJECTION
 TITLE
 DOUBLE ENDED MHV CONNECTOR



REV.	APP'D	DATE	SCALE 1.5:1	DIMENSIONS IN INCHES [mm]	DRAWN	JM	1/25/2006
E1	CW	4/6/2022	COMH0007-01		ENG APPR.	CW	4/6/2022

PART NO. FA11314 REV. E

WWW.SOLIDSEALING.COM

SALES DWG NO. FA11314SL REV. E1

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.