

PART NO.	AIR SIDE PLUG/CABLE
FA11502	NO
KT11502	YES

RATINGS	
VOLTAGE:	1KV DC
CURRENT:	2 AMPS
PRESSURE:	1600 PSIG @ 20°C
TEMPERATURE WITHOUT PLUG:	-80°C TO 450°C*
TEMPERATURE WITH PLUG:	-40°C TO 75°C

\* CALL SST TO CONFIRM LOWER TEMPERATURE USE

[WWW.SOLIDSEALING.COM](http://WWW.SOLIDSEALING.COM)




**SOLID SEALING TECHNOLOGY, INC.**

SALES DWG NO. FA11502SL REV. B2

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

MICRODOT CONNECTOR

PART NO. FA11502 REV. B

REV.	APP'D	DATE	SCALE 8:1	DIMENSIONS IN INCHES [mm]	DRAWN	JM	1/25/2006
B2	JF	03/20/2014	COMC0001-01		ENG APPR.	MH	03/21/2006