

| FREQUENCY | CURRENT |
|-----------|----------|
| 100 KHz | 300 AMPS |
| 300 KHz | 250 AMPS |
| 450 KHz | 200 AMPS |
| 13.56 MHz | 100 AMPS |

| RATINGS | |
|--------------|-------------------|
| VOLTAGE: | 14KV DC |
| FREQUENCY: | SEE TABLE AT LEFT |
| CURRENT: | SEE TABLE AT LEFT |
| PRESSURE: | 500 PSIG @ 20°C |
| TEMPERATURE: | -55°C TO 350°C |

WWW.SOLIDSEALING.COM




SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA11559SL REV. A2

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

RF FEEDTHROUGH

PART NO. FA11559 REV. A

| REV. | APP'D | DATE | SCALE 1:1 | DIMENSIONS IN INCHES [mm] | DRAWN | JM | 4/12/2006 |
|------|-------|------------|-------------|---------------------------|-----------|----|------------|
| A2 | JS | 11/27/2012 | FTST0009-01 | | ENG APPR. | MH | 08/11/2006 |

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.