



PART NO.	CONDUCTOR MATERIAL
FA11631	CHROMEL
FA11631-02	IRON
FA11631-03	TUNGSTEN 5% RHENIUM*

*USES COMPENSATING WIRE
 MAXIMUM JUNCTION TEMPERATURE 250°C

PERFORMANCE SPECIFICATIONS	
CONDUCTOR MATERIAL:	SEE TABLE AT LEFT
PRESSURE:	3500 PSIG @ 20°C
TEMPERATURE WITHOUT PLUG:	-269°C TO 450°C
TEMPERATURE WITH PLUG:	-29°C TO 218°C

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 		TITLE SINGLE LEG T/C (+) SPADE TYPE			
REV.	APP'D	DATE	SCALE 1.25:1	DIMENSIONS IN INCHES [mm]	DRAWN	JM	1/12/2006	PART NO. (SEE TABLE) REV. B	WWW.SOLIDSEALING.COM
B1	CW	11/15/2021	FTCL0025-ST		ENG APPR.	MH	05/26/2006		SALES DWG NO. FA11631SL REV. B1

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.