



| PART NO. | CONDUCTOR MATERIAL |
|------------|-----------------------|
| FA11632 | ALUMEL |
| FA11632-02 | CONSTANTAN |
| FA11632-03 | TUNGSTEN 26% RHENIUM* |

*USES COMPENSATING WIRE
 MAXIMUM JUNCTION TEMPERATURE 250°C

| PERFORMANCE SPECIFICATIONS | |
|----------------------------|-------------------|
| CONDUCTOR MATERIAL: | SEE TABLE AT LEFT |
| PRESSURE: | 3500 PSIG @ 20°C |
| TEMPERATURE WITHOUT PLUG: | -269°C TO 450°C |
| TEMPERATURE WITH PLUG: | -29°C TO 218°C |

| | | | | | | | | | |
|--|-------|------------|--------------|----------------------------|-----------|------------------------------------|------------|-----------------------------|---------------------------------|
| PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED. | | | | THIRD ANGLE PROJECTION | | TITLE SINGLE LEG (-) SPADE TYPE | | | |
| REV. | APP'D | DATE | SCALE 1.25:1 | DIMENSIONS IN INCHES [mm] | DRAWN | JM | 1/12/2006 | PART NO. (SEE TABLE) REV. B | WWW.SOLIDSEALING.COM |
| B1 | CW | 11/15/2021 | FTCL0024-ST | | ENG APPR. | MH | 05/26/2006 | | SALES DWG NO. FA11632SL REV. B1 |

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.