

| PART NO. | CONDUCTOR MATERIAL | CURRENT |
|------------|--------------------|----------|
| FA11637 | COPPER | 16 AMPS |
| FA11637-02 | MOLYBDENUM | 8.5 AMPS |
| FA11637-03 | NICKEL 200 | 5 AMPS |
| FA11637-04 | 304 STN STL | 1.1 AMPS |

| RATINGS | |
|--------------|-------------------|
| VOLTAGE: | 2 KV DC |
| CURRENT: | SEE TABLE AT LEFT |
| PRESSURE: | 0 PSIG @ 20°C* |
| TEMPERATURE: | -25°C TO 205°C |

*FOR INTERNAL PRESSURE 5 TO 100 PSIG
AN OVERPRESSURE RING IS REQUIRED.

WWW.SOLIDSEALING.COM




SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA11637SL REV. A2

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

TWO 2KV FEEDTHROUGHS

PART NO. (SEE TABLE) REV. A

| REV. | APP'D | DATE | SCALE 3:2 | DIMENSIONS IN INCHES [mm] | DRAWN | JM | 12/27/2005 |
|------|-------|------------|--------------|---------------------------|-----------|----|------------|
| A2 | JS | 05/01/2013 | MPDC0004-0ST | | ENG APPR. | MH | 03/21/2006 |

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.