



PART NO.	CONDUCTR MATERIAL	CURRENT
FA11638	COPPER	16 AMPS
FA11638-02	MOLYBDENUM	8.5 AMPS
FA11638-03	NICKEL	5 AMPS
FA11638-04	304 STN STL	1.1 AMPS

RATINGS	
VOLTAGE:	2 KV DC
CURRENT:	SEE TABLE AT LEFT
PRESSURE:	1400 PSIG @ 20°C
TEMPERATURE:	-269°C TO 450°C

WWW.SOLIDSEALING.COM



SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA11638SL REV. A2

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

TWO 2KV FEEDTHROUGHS

PART NO. (SEE TABLE) REV. A

REV.	APP'D	DATE	SCALE 2:1	DIMENSIONS IN INCHES [mm]	DRAWN	JM	12/27/2005
A2	JS	05/01/2013	MPDC0005-0ST		ENG APPR.	MH	03/21/2006

**DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.**