



| PART NO. | CONDUCTOR MATERIAL | CURRENT |
|------------|--------------------|----------|
| FA11640 | COPPER | 16 AMPS |
| FA11640-02 | MOLYBDENUM | 8.5 AMPS |
| FA11640-03 | NICKEL | 5 AMPS |
| FA11640-04 | 304 STN STL | 1.1 AMPS |

| RATINGS | |
|--------------|-------------------|
| VOLTAGE: | 2 KV DC |
| CURRENT: | SEE TABLE AT LEFT |
| PRESSURE: | 1400 PSIG @ 20°C |
| TEMPERATURE: | -269°C TO 450°C |

WWW.SOLIDSEALING.COM



SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA11640SL REV. A2

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

FOUR 2KV FEEDTHROUGHS

PART NO. FA11640 REV. A

| REV. | APP'D | DATE | SCALE 2:1 | DIMENSIONS IN INCHES [mm] | DRAWN | JM | 1/12/2006 |
|------|-------|------------|-------------|---------------------------|-----------|----|------------|
| A2 | JS | 05/01/2013 | MPDC0007-01 | | ENG APPR. | MH | 03/21/2006 |

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.