

PART NO.	CONDUCTOR MATERIAL	CURRENT
FA11649	COPPER	27 AMPS
FA11649-02	MOLYBDENUM	13.5 AMPS
FA11649-03	NICKEL	8.2 AMPS
FA11649-04	304 STN STL	1.8 AMPS

RATINGS	
VOLTAGE:	6KV DC
CURRENT:	SEE TABLE AT LEFT
PRESSURE:	0 PSIG @ 20°C*
TEMPERATURE:	-25°C TO 205°C

*FOR INTERNAL PRESURE 5 TO 100 PSIG AN OVERPRESSURE RING IS REQUIRED.

WWW.SOLIDSEALING.COM




SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA11649SL REV. A2

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

FOUR 6KV FEEDTHROUGHS

PART NO. FA11649 REV. A

REV.	APP'D	DATE	SCALE 1:0.666667	DIMENSIONS IN INCHES [mm]	DRAWN	JM	2/15/2006
A2	JS	05/02/2013	MPCL0021-02		ENG APPR.	MH	08/24/2006

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.