



PART NO.	CONDUCTOR MATERIAL	T/C TYPE	POWER LEAD MATERIAL	CURRENT
FA11651	CHROMEL / ALUMEL	K	COPPER	27 AMPS
FA11651-02	IRON / CONSTANTAN	J	COPPER	27 AMPS
FA11651-03	TUNGSTEN / RHENIUM*	C	COPPER	27 AMPS
FA11651-04	CHROMEL / CONSTANTAN	E	COPPER	27 AMPS
FA11651-05	CHROMEL / ALUMEL	K	NICKEL	8.2 AMPS
FA11651-06	IRON / CONSTANTAN	J	NICKEL	8.2 AMPS
FA11651-07	TUNGSTEN / RHENIUM*	C	NICKEL	8.2 AMPS
FA11651-08	CHROMEL / CONSTANTAN	E	NICKEL	8.2 AMPS

RATINGS	
VOLTAGE:	3KV DC
CONDUCTOR MATERIAL:	SEE TABLE AT LEFT
T/C TYPE:	SEE TABLE AT LEFT
POWER LEAD MATERIAL:	SEE TABLE AT LEFT
CURRENT:	SEE TABLE AT LEFT
PRESSURE:	800 PSIG @ 20°C
TEMPERATURE WITHOUT PLUG:	-269°C TO 450°C
TEMPERATURE WITH PLUG:	-29°C TO 218°C

\*TYPE C USES COMPENSATING WIRE. MAXIMUM JUNCTION TEMPERATURE 250°C

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 		TITLE: <b>T/C SPADE TYPE &amp; 3KV POWER</b>		<a href="http://WWW.SOLIDSEALING.COM">WWW.SOLIDSEALING.COM</a> 	
REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	JM	1/12/2006	PART NO. (SEE TABLE) REV. B	
B2	JS	05/24/2013	MPL0046-ST		ENG APPR.	MH	05/26/2006		

**DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.**