



PART NO.	CONDUCTOR MATERIAL	CURRENT
FA11666	COPPER	55 AMPS
FA11666-02	MOLYBDENUM	28 AMPS
FA11666-03	NICKEL	16.5 AMPS
FA11666-04	304 STN STL	3.6 AMPS

PERFORMANCE SPECIFICATIONS	
VOLTAGE:	5KV DC
CURRENT:	SEE TABLE AT LEFT
PRESSURE:	1500 PSIG @ 20°C
TEMPERATURE:	-269°C TO 450°C

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 		TITLE TWO 5KV FEEDTHROUGHS			
REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	JM	2/15/2006	PART NO. (SEE TABLE) REV. C	WWW.SOLIDSEALING.COM
C1	JF	09/22/2021	FTST0024-ST		ENG APPR.	MH	08/24/2006		SALES DWG NO. FA11666SL REV. C1

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.