



PART NO.	CONDUCTOR MATERIAL	CURRENT
FA11672	COPPER	55 AMPS
FA11672-02	MOLYBDENUM	28 AMPS
FA11672-03	NICKEL	16.5 AMPS
FA11672-04	304 STN STL	3.6 AMPS

RATINGS	
VOLTAGE:	5KV DC
CURRENT:	SEE TABLE AT LEFT
PRESSURE:	1500 PSIG @ 20°C
TEMPERATURE:	-269°C TO 450°C

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 			TITLE: FOUR 5KV FEEDTHROUGHS		WWW.SOLIDSEALING.COM 		
REV.	APP'D	DATE	SCALE 4:5	DIMENSIONS IN INCHES [mm]	DRAWN	JM	1/12/2006	PART NO. FA11672 REV. A		SOLID SEALING TECHNOLOGY, INC.	
A2	JS	05/02/2013	MPST0011-11	ENG APPR.	MH	04/28/2006	SALES DWG NO. FA11672SL REV. A2				

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.