



PART NO.	CONDUCTOR MATERIAL	T/C TYPE
FA11685	PLATINUM/ RHODIUM*	R/S
FA11685-02	COPPER/ CONSTANTAN	T

*TYPE R/S USES COMPENSATING WIRE
 MAXIMUM JUNCTION TEMPERATURE 250°C

RATINGS	
CONDUCTOR MATERIAL:	SEE TABLE AT LEFT
T/C TYPE:	SEE TABLE AT LEFT
PRESSURE:	800 PSIG @ 20°C
TEMPERATURE:	-269°C TO 450°C

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 			TITLE: DUAL LOOP T/C FEEDTHROUGH		WWW.SOLIDSEALING.COM 	
REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	JM	1/12/2006	PART NO. (SEE TABLE) REV. B		
B2	JS	05/24/2013	MPCL0028-ST		ENG APPR.	MH	05/26/2006			SOLID SEALING TECHNOLOGY, INC. SALES DWG NO. FA11685SL REV. B2

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.