



PART NO.	CONDUCTOR MATERIAL	T/C TYPE
FA11694	CHROMEL / ALUMEL	K
FA11694-02	IRON / CONSTANTAN	J
FA11694-03	TUNGSTEN / RHENIUM*	C
FA11694-04	CHROMEL / CONSTANTAN	E

*TYPE C USES COMPENSATION WIRE
 MAXIMUM JUNCTION TEMPERATURE 250°C

RATINGS	
CONDUCTOR MATERIAL:	SEE TABLE AT LEFT
T/C TYPE:	SEE TABLE AT LEFT
PRESSURE:	0 PSIG @ 20°C*
TEMPERATURE:	-25°C TO 205°C

* FOR INTERNAL PRESSURE 5 TO 100 PSIG
 AN OVERPRESSURE RING IS REQUIRED.

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 			TITLE: SINGLE PAIR SPADE FEEDTHROUGH		WWW.SOLIDSEALING.COM 	
REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	JM	1/13/2006	PART NO. (SEE TABLE) REV. A		
A2	JS	06/11/2013	MPCL0025-ST		ENG APPR.	MH	05/26/2006			SOLID SEALING TECHNOLOGY, INC. SALES DWG NO. FA11694SL REV. A2