

PART NO.	CONDUCTOR MATERIAL	T/C TYPE
FA11697	PLATINUM / RHODIUM*	R/S
FA11697-02	COPPER / CONSTANTAN	T

\*TYPE R/S USES COMPENSATING WIRE  
 MAXIMUM JUNCTION TEMPERATURE 250°C

RATINGS	
CONDUCTOR MATERIAL:	SEE TABLE AT LEFT
T/C TYPE:	SEE TABLE AT LEFT
PRESSURE:	0 PSIG @ 20°C*
TEMPERATURE:	-25°C TO 205°C

\*FOR INTERNAL PRESURE 5 TO 100 PSIG  
 AN OVERPRESSURE RING IS REQUIRED.

[WWW.SOLIDSEALING.COM](http://WWW.SOLIDSEALING.COM)




**SOLID SEALING TECHNOLOGY, INC.**

SALES DWG NO. FA11697SL REV. B2

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE  
 SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY  
 REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN  
 PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

DUAL LOOP T/C FEEDTHROUGH

PART NO. (SEE TABLE) REV. B

REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	JM	1/13/2006
B2	JS	05/24/2013	MPCL0029-ST		ENG APPR.	MH	05/26/2006

**DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.**