



PART No.	CONDUCTOR MATERIAL	CURRENT
FA11715	COPPER	185 AMPS
FA11715-02	MOLYBDEDENUM	93 AMPS
FA11715-03	NICKEL	56 AMPS
FA11715-04	304 STN STL	12 AMPS

PERFORMANCE SPECIFICATIONS	
VOLTAGE:	12 KV DC
CURRENT:	SEE TABLE AT LEFT
PRESSURE:	0 PSIG @ 20°C*
TEMPERATURE:	-25°C TO 205°C

*FOR INTERNAL PRESSURE 5 TO 100 SPIG AN OVERPRESSURE RING IS REQUIRED

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 		TITLE THREE 12KV FEEDTHRUS ON KF40				
REV.	APP'D	DATE	SCALE 7:8	DIMENSIONS IN INCHES [mm]	DRAWN	MH	4/2/2024	PART NO. (SEE TABLE) REV. A		WWW.SOLIDSEALING.COM
A2	JF	04/02/2024	FTST0276-1ST		ENG APPR.	MH	4/2/2024			SALES DWG NO. FA11715SL REV. A2

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.