

PART NO.	CONDUCTOR MATERIAL	CURRENT
FA11823	COPPER	55 AMPS
FA11823-02	MOLYBDENUM	28 AMPS
FA11823-03	NICKEL	16.5 AMPS
FA11823-04	304 STN STL	3.6 AMPS

RATINGS	
VOLTAGE:	14KV DC
CURRENT:	SEE TABLE AT LEFT
PRESSURE:	0 PSIG @ 20°C*
TEMPERATURE:	-25°C TO 205°C

*FOR INTERNAL PRESSURE 5 TO 100 PSIG AN OVERPRESSURE RING IS REQUIRED.

WWW.SOLIDSEALING.COM




SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA11823SL REV. A2

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

FOUR 14KV FEEDTHROUGHS

PART NO. (SEE TABLE) REV. A

REV.	APP'D	DATE	SCALE 1:1.33333	DIMENSIONS IN INCHES [mm]	DRAWN	JM	4/12/2006
A2	JS	05/02/2013	FTST0018-ST		ENG APPR.	MH	08/11/2006

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.