

PART NO.	CONDUCTOR MATERIAL	CURRENT
FA12011	COPPER	55 AMPS
FA12011-03	NICKEL	16.5 AMPS
FA12011-04	304 STN STL	3.6 AMPS

RATINGS	
VOLTAGE:	20KV DC
CURRENT:	SEE TABLE AT LEFT
PRESSURE:	250 PSIG @ 20°C
TEMPERATURE:	-269°C TO 450°C

WWW.SOLIDSEALING.COM




SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA12011SL REV. E1

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

HV FEEDTHROUGH

PART NO. (SEE TABLE) REV. E

REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	MH	04/04/2006
E1	JF	05/18/2015	FCCL0027-0ST		ENG APPR.	JF	05/18/2015

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.