


PART NO.	CONDUCTOR MATERIAL	CURRENT
FA12077	COPPER	55 AMPS
FA12077-02	MOLYBDENUM	28 AMPS
FA12077-03	NICKEL	16.5 AMPS
FA12077-04	304 STN STL	3.6 AMPS

RATINGS	
VOLTAGE:	2KV DC
CURRENT:	SEE TABLE AT LEFT
PRESSURE:	200 PSIG @ 20°C
TEMPERATURE:	-25°C TO 205°C

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

2KV BASEPLATE FEEDTHRU

WWW.SOLIDSEALING.COM



SOLID SEALING TECHNOLOGY, INC.

REV.	APP'D	DATE	SCALE 3:4	DIMENSIONS IN INCHES [mm]	DRAWN	JS	3/21/2008
C2	JS	09/24/2012	MPST0009-ST		ENG APPR.	MH	06/10/2008

PART NO. (SEE TABLE) REV. C

SALES DWG NO. FA12077SL REV. C2

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.